

ASTM D 892 - D 6082 - ISO 6247 - IP 146

SCOPE

Standard Test Method for Foaming Characteristics of Lubricating Oils

HIGH TEMPERATURE FOAMING CHARACTERISTICS OF LUBRICATING OILS

- **FOAM HT CLASSIC** -
- **REF 9416432** -

MAIN CHARACTERISTICS

- ✓ Test bath for 2 tests up to 150°C (24°C- 93°C- 150°C)
- ✓ The bath is placed in a highly protective cage.
- ✓ The bath complies with sequence I, II, III and IV of ASTM D892 & D6082

SCOPE OF DELIVERY

FOAM HT CLASSIC delivered ready for use with :

REF 11523	One thermometer 41 C
REF 9000423	Two calibrated flowmeters
2 X REF 9416412	Graduated cylinder - 1000 ml- (Ref : 19371) with ring ballast
REF 9417905	Pt 100 probe (250 x 5 mm)

OPTIONS ACCESSORIES FOAM SEQUENCER

REF 9416434	Oil polyalphaolefin for bath (can of 25 liters)
REF 9416401	Drying tower for 9416432 - Ready to use -
REF 941644	Wet test gas meter, TG 05 (280x230x300mm) / ±8kg
REF 22239	Cooling cryostat (-28/+100°C ±0.02)
REF 9426433	New air compressor - 230 V -
REF 24803	Stainless steel diffuser



REF 9416401

INFORMATION DE COMMANDE

REF 9416432
AC 230 V, 50 Hz - 10 A

(W) 750x (D) 350x (H) 760 mm (±30 kg)

CONTACT : sales@normalab.com

NORMALAB FRANCE SAS
ZA Caux Multipôles 1 - F-76 190 Valliquerville
Tel. : +33 232 700 100
Fax : +33 232 704 732

www.normalab.com

REF 9416432 Leaflet 15

DISTRIBUTED BY

G-Labo Germany
Bgm.-Horneffstr.26
69509 Mörlenbach
Tel.: + 49 6209 797100
Fax: + 49 6209 797101
Mail: info@g-labo.de
Web: www.g-labo.de